



## VINTIGO 220.01 4X

### Product description

One system, four stunning colors. Exclusive product with an extremely high resistance, yet the appearance of aged wood.

### Technical data

Article name:	Vintigo®
Article no.:	220.014X
Efficiency:	ca. 7-12 m <sup>2</sup> /lt. (150 g/m <sup>2</sup> )
Packaging:	Tin 10 lt. + inliner / IBC



Viscosity:	15-18 DIN-4mm
------------	---------------

Application technology:	Airgun: pressure (BAR) 2-3, Spraying nozzle (mm): 1,5-1,8. Dipping or brush.
-------------------------	--



Drying times (20 °C, RV 45-60%):	Minimum of 8 hours, we require overnight.
----------------------------------	---

After treatment:	Q-oil® or Zero lacquer® system
------------------	--------------------------------



Storage stability:	Under normal conditions in unopened packaging 3 months
Storage stability:	Has a limited shelf life after opening

Remaining article numbers:	Special Bleaching Agent <b>000.0221</b> Old White Patina <b>500.0206</b> Water based sealer <b>800.0469</b> Zero Magnum <b>800.0446</b> Water based hardener <b>800.0449</b>
----------------------------	--

### Pre-treatment

Can be used on planed, sanded or brushed wood. We prefer brushed wood due to the fact that the Old White Patina will be visible as much as possible.

### Processing

**Step 1:** Apply Vintigo evenly, let the air do its work and dry through the night - which is also necessary for the coming 3 steps.

**Step 2:** Apply 'Special bleaching agent' evenly, let it dry;

**Step 3:** Apply 'Old white patina', let it sit for approx. 15 min. Wipe away the excess and let it dry.

'Vintigo Sealer' and 'Zero Magnum' is required to make the patina stand out well. That being said, on to the last two steps:

**Step 4:** Sand the surface with a fine grain as much as you prefer and apply one layer of 'Vintigo Sealer', again; let it dry;

**Step 5:** No one likes dirty stains on to their surface. Therefore we apply 3 layers of Zero Magnum or any of our water based system. Don't forget sanding between the 2<sup>nd</sup> and 3<sup>rd</sup> layer! This lacquer dries fast, contact us for more information.

### Drying time

Allow to dry overnight at a room temperature of 20°C and a relative humidity of 45 - 60%. The effect will be less if you force the drying time.

### Finish

After complete drying, the surface can be finished with Quartier lacquers or oils - please contact the sales department.

### Particularities

Water based products are sensitive to frost, do not transport or store <5 °C. Only use with stainless material. The final effect of this stain can only be assessed after finishing. The final color depends on the preparation, type of wood and finish.

### Efficiency & storage

The efficiency is 7-12 m<sup>2</sup> / liter, this depends on the type of wood and application method. The storage stability in original packaging is 3 months. This product is only intended for professional use.

Date of issue: 24-01-2020



Vintigo A



Vintigo B



Vintigo C



Vintigo D

### TECHNICAL INFORMATION SHEET

Brochures and advice are provided without obligation. As the method of application and the circumstances involved fall outside of our assessment, no liability can be accepted based on the information provided. All our deliveries, recommendations, documentation, etc., are subject to the terms and conditions of sale and delivery filed with the Chamber of Commerce. (Chamber of Commerce, Veluwe and Twente no. 06089530)